



HIGH PRESSURE FITTING SUBMITTAL

MATERIAL:

All high-pressure fittings are fabricated from Commercial Grade *G60/G90* galvanized coating, conforming to ASTM A90, A568, A653, A924. All fittings are fabricated to code or customer specified code and gauges.

Stainless Steel, Aluminum, Galvanized, Paintable Galvanized and other materials are available upon request.

FABRICATION:

Elbows and fittings are fabricated on a rotary machine using a 3/8" offset to assure air flow efficiency and strength. All fittings are fabricated with a 2" minimum slip fit end to assure tightness of installation.

Fittings are either spot or tack welded 1" centerline and pressure sealed or continuous welded upon customer request. Elbows are long radius (1.5 x centerline) or short radius using a minimum of 2 gores.

All fittings are fabricated for 8" positive static pressure and 2" negative static pressure conforming to SMACNA HV AC Duct Construction Standards, SMACNA Industrial Duct Construction Standards and Uniform Mechanical Code. Other static pressure system gauges are available upon request.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

5200 E. La Palma
Anaheim, CA 92807
(888) Eco-Duct (326-3828)
Fax: 714-970-3976

URL: www.ecoduct.com
Email: Sales@ecoduct.com

21005 Cabot Blvd.
Hayward, CA 94545
(510) 670-0326 Phone
(510) 670-0384 Fax