



## LOW PRESSURE FITTING SUBMITTAL

---

### **MATERIAL:**

All low pressure fittings are fabricated from Commercial Grade G60/G90 galvanized coating, conforming to ASTM A90, A568, A653, A924. All fittings are fabricated to code or customer code and gauge.

Stainless Steel, Aluminum, Galvanized, Paintable Galvanized and other materials are available upon request.

### **FABRICATION:**

Adjustable elbows are fabricated on a rotary machine using a 3/8 inch offset swivel for adjustability. All other fittings are fabricated with an overlap, flange branch or joint to assure strength. Elbows and fittings are fabricated with either male/female, female/female or slip fit ends to assure tightness and ease of installation. All elbows and fittings are either spot welded, riveted or stapled approximately 3" centerline to conform to SMACNA Standards and Uniform Mechanical Commercial Codes. All Low Pressure Fittings are available with pressure seam sealer upon request.

*Specifications subject to change without notice*

5200 E. La Palma  
Anaheim, CA 92807  
(888) Eco-Duct (326-3828)  
Fax: 714-970-3976

URL: [www.ecoduct.com](http://www.ecoduct.com)  
Email: [Sales@ecoduct.com](mailto:Sales@ecoduct.com)

21005 Cabot Blvd.  
Hayward, CA 94545  
(510) 670-0326 Phone  
(510) 670-0384 Fax